

# INSTALLATION INSTRUCTIONS

Item# 16014X-XXX-L

## READ AND SAVE THESE INSTRUCTIONS

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**  
**AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

### HANGING THE FIXTURE (Fig. 1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
3. Thread screw (B) into mounting plate (C) spaced the same distance apart as the holes on canopy (F). The length of screw (B) may be adjusted if necessary. Attach the mounting plate (C) to the junction box using the mounting screws (D) (size: 8/32\*25mm). The side of the mounting plate marked "GND" must face out.

### CONNECTING THE WIRES (Fig. 2)

4. Connect the electrical wires as shown in (Fig.2), making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect the fixture ground wire to it. After the wires are connected, tuck them carefully inside the junction box.

### FINISH THE INSTALLATION (Fig. 1)

5. Place the canopy (F) onto the mounting screws (B) and secure with the cap nuts (K).
6. Align the holes on the side panel (I) with those on the Ring (M) and Ring (H), and secure them with Screws (G) and Screws(O) respectively, Insert the glass (L) into the Ring (M) and Ring (H).
7. Finally, align the glass frame assembly with the mounting holes on the canopy (F), and secure the assembly using the specified screws (J).

### Replacing LED module (Fig.3)

The LED module can be replaced by a qualified electrician without cutting of wire and without damage to any decorative element to which the fixture is attached. See installation steps for more details (Fig.3).

- a. Shut off the power.
- b. Unscrew (J) to remove the glass frame assembly from the canopy(F).
- c. To remove the fixture from the ceiling: loosen the cap nuts (K) and remove the wire connectors (E) . Then place the fixture on a clear flat surface (Fig.3)
- d. Loosen the screws (P) and washer & hex nuts, remove the LED module (N) from the canopy (F).
- e. Reverse steps b-d for installing the new LED module.

Your installation is complete now. Return power to the junction box and test the fixture.

**Note:** Illustration (Fig.1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

**IMPORTANT: FIXTURE SHOULD BE INSTALLED BY A QUALIFIED ELECTRICIAN TO ENSURE PROPER WIRING AND INSTALLATION.**

Dimmable with ELV and/or LED compatible wall dimmer switches.

The LED module includes 5CCTs (2700K/3000K/3500K/4000K/5000K), please select the desired color temperature before installation.

