

# INSTALLATION INSTRUCTIONS

Item# N1525-860

READ AND SAVE THESE INSTRUCTIONS

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**  
**VERTISEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

## ASSEMBLING THE FIXTURE (Fig.1 & Fig.2)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clean area. Take care not to misplace any small parts necessary for installation.
3. Remove the mounting plate (A) from the canopy (D) by removing the screw (C) located on the side of canopy (D).
4. Attached mounting plate (A) to junction box (JB) (*not provided*) with # 8-32 mounting screws (B). The side of mounting plate (A) marked with "GND" must be face out.

## HANGING THE FIXTURE (Fig.1)

5. Thread the center rod (E) onto coupler (1) and secure swivel of canopy (D) into center rod (E) with hex nut and washer until tight.

## CONNECTING THE WIRE (Fig. 3)

6. Connect the electrical wire as shown in Fig. 3, making sure that all the wire connectors are secured. If your junction box has a ground wire (green, or bare copper), connect fixture's ground wire to it. Otherwise, connect fixture's ground wire directly to mounting plate (A) using green screw provided.
7. Tuck wire connections neatly into junction box (JB). Fig.2.
8. Raise the canopy (D) to fit on the mounting plate (A) and secure with side screws (C).

## ACCESSORIES INSTALLATION (Fig. 1)

9. Attach the hook of 3 stems (F) onto the hook of sub-canopy (D) and the hook of frame (H).
10. To begin installing the accessories unwrap the ceramic wavy disc (I) from the packing.
11. To begin installing, place the hole of the ceramic wavy disc (I) (with arrow C) into the threaded round tube (with arrow) and secure with rubber washers provided and (G). Do not over tighten. Note we have 4 kinds of ceramic (A,B,C,D).
12. Repeat the process until completed.

## FINISHING THE FIXTURE (FIG. 1)

13. Install (5) five candelabra base bulbs up to 60 watts each of CFL or LED equivalent (not included) in accordance to fixture specifications.

**DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**  
**(NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**

Your installation is now complete. You can now turn the power ON and test the fixture.

**Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.**

