

INSTALLATION INSTRUCTIONS

Item# N1835-870

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
VERTISEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

ASSEMBLING THE FIXTURE (Fig. 1&2)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clean area. Ensure not to misplace any small part necessary for installation.
3. Remove mounting plate (A) from canopy (F) by removing the decorative ball nuts (G) located on canopy (F).
4. Attach mounting plate (A) to the junction box (JB) (*Not provided*) with junction box screws (B). The side of mounting plate (A) with marked "GND" and two convex points must face out.

HANGING THE FIXTURE (Fig. 1)

5. When assembling the main frame, slip the wire of distributor (J) into the center stem (I), upper frame and attach the center stem (I) on the upper frame.
6. Slip the wire into the stem (H) then into canopy (F)
7. Lock the canopy (F) into the stem (H) using lock washer (E), support cable ring and hex nut (D).
8. The support cable (SC) is provided to support the weight of the fixture while wiring. Align the fixture to mounting plate (A) and attach hook (HK) on the end of support cable (SC) into a slot located on mounting plate (A). Carefully allow the support cable (SC) to support the weight of the fixture while wiring.

CONNECTING THE WIRE (Fig. 3)

9. Connect the electrical wire as shown in Fig. 2, making sure that all the wire connectors are secured. If your junction box has a ground wire (green, or bare copper), connect fixture's ground wire to it. Otherwise, connect fixture's ground wire directly to mounting plate using green screw provided.
10. Tuck wire connections neatly into junction box (JB).
11. Insert the mounting plate screw (C) to the hole of the canopy (F) then lock with ball knob (G).

ACCESSORIES INSTALLATION (Fig. 4)

12. To begin installing the accessories unwrap the accessories strands (K) and accessories strand (L) from the packing.
13. Place the pin of the first accessories strands (K) into the hole of the frame then then the first strand of accessories strands (L).
14. Repeat the process until completed.

FINISHING THE FIXTURE

15. Install (5) five candelabra base bulbs up to 60 watts each of CFL or LED equivalent (not included) in accordance to fixture specifications.

DO NOT EXCEED THE MAXIMUM WATTAGE RATING!
(NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

Your installation is now complete. You can now turn the power ON and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

The fixture is over 10 lbs., please remove the strands (K and L) (before removing canopy from the mounting plate (A) to inspect wire connectors in the future. This will allow you to hold the fixture body during wire connection or inspection or fixture removal.

