

INSTALLATION INSTRUCTION FOR P1802

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

READ AND SAVE THESE INSTRUCTIONS

PREPARATION

1. Shut off the power at the circuit breaker and remove the old fixture, including the mounting hardware.
2. Carefully remove the fixture from the carton and check that all parts are included as shown in the illustration.

ASSEMBLING THE FIXTURE(Fig.1)

3. Thread the decorative stems (G) into the main body (F).

MOUNTING THE FIXTURE (Fig.1)

4. Thread the two mounting screws (A) (Size: #8-32*1.6"L) part way into the circular strap (B). Secure circular strap (B) to the junction box (not provided) with junction box screws (C) (Size: #8-32*0.6"L). The length of mounting screws (A) into circular strap (B) may be adjusted if necessary.

CONNECTING THE WIRES (Fig. 2)

5. At this point, connect the electrical wires as shown in Fig. 2 making sure all wire connectors are secured. If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate using the green screw provided. After the wires are connected, tuck them neatly inside the junction box.

COMPLETING THE INSTALLATION

6. Mount the fixture body (D) to mounting screws (A) and secure with finials (E).
7. Align glass shades (I) followed by spacers (J) over sockets (H) and secure with socket rings (K) via the wrench provided (M).
8. Install the light bulbs (L) (Supplied) in accordance with the fixture's specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**

Your installation is now complete. Return the power to the junction box and test the fixture.

Fig.1




Fig.2

