MINKA
AIRE

Pairing your AC Motor Fan

Connect a Minka-Aire hand-held remote or wall control to your fan receiver in four steps.

WHAT YOU NEED



Hand-held remote

or



Wall control

+



Receiver

This fan will not operate without a control, a receiver and proper pairing. The receiver installs in the fan canopy.

PAIR IN FOUR STEPS

1–2 min
power off

1 Reset the receiver

Turn the power to the fan off for 1 to 2 minutes to de-energize the receiver, then turn it back on.



2 Set a unique code

Set the control's dip switches to a pattern no other control in your home uses. Hand-held: above the battery. Wall control: behind the face plate.



3 Pair the control

Within the 60-second pairing window after restoring power, press and hold the square stop button for 10 to 15 seconds. If pairing is successful, the light blinks two or three times, then the fan motor will operate for a short period of time before turning off.



4 Test the fan

Check the fan speeds (one-, two- and three-dot buttons) and the light (top button). Reverse (if your control has it) works only while the fan is running.

More than one fan?

Power only one fan at a time. Give each control its own dip-switch pattern. After pairing, turn that fan's power off at the circuit or switch, then repeat steps 1–4 for the next fan.

Once all fans are paired, restore power to all fans and check pairing and operation.

Fan not responding? Turn the power off and repeat the process from step 1.