



Image File Name: F678L-GRY.jpg

Twist - LED 52" Ceiling Fan



Integrated Smart Control

LED

LED



ETL Listed

Item #: F678L-GRY

UPC Code: 706411068553

Collection: Twist

Category: Fan

Product Type: Fan

Subtype: Ceiling Fan

Descriptive Finish 1: Grey

ETL Certificate: 3064964

MEASUREMENTS

| | |
|--------------------------|----------|
| Length: | 52.00 |
| Width: | 52.00 |
| Height: | 14.50 |
| Product Weight: | 11.24 |
| Ceiling to Blade: | 9.50 |
| Ceiling to Lowest Point: | 14.50 |
| Downrod Included: | Yes |
| Downrod Length 1: | 6.00 |
| Downrod Width 1: | 0.75 |
| Cord Length: | 80 |
| Wire Length: | 80 |
| Blade Finish: | Grey |
| Blade Material: | ABS |
| Slope: | Yes |
| Reversible Rotation: | Yes |
| Number of Blades: | 3 |
| Blade Pitch: | 16 |
| Blade Sweep: | 52 |
| Reversible Blades: | No |
| Number of Speeds: | 6 |
| Motor Size: | 120x15mm |
| Motor Type: | DC |

LAMPING

| | |
|------------------------|----------------|
| Light Type 1: | LED |
| LED: | Yes |
| Bulb Base 1: | Integrated |
| Bulb Type 1: | Integrated LED |
| Bulb Included: | No |
| Bulb Wattage: | 20 |
| Dimmable: | Yes |
| Initial Lumens: | 1572 |
| Delivered Lumens: | 1049.1 |
| Color Rendering Index: | 94 |
| Rated Life Hours: | 20000 |
| Light Kit Compatible: | No |
| Light Kit Included: | Yes |

GLASS

| | |
|-------------------|--------------------|
| Shade Finish: | White Lens |
| Shade Material: | Polycarbonate Lens |
| SHIPPING | |
| Cartons Per Unit: | 1 |
| Case Pack: | 1 |
| Ship Length: | 32.88 |
| Ship Width: | 13.00 |
| Ship Height: | 9.63 |
| Ship Weight: | 15.40 |
| Ship Volume: | 2.382 |
| Small Parcel: | Yes |

CONTROLS

| | |
|---------------------------|--------|
| Pull Chain Control: | No |
| Remote Included: | Yes |
| Remote Control SKU: | RC1000 |
| Wall Control Included: | No |
| Compatible Wall Controls: | WC1000 |

Integrated Smart Control: Yes

| | Low | L/M | Medium | M/H | High |
|-----------|--------|-----|--------|-----|--------|
| RPM | 53 | | | | 148 |
| Amps | 0.09 | | | | 0.53 |
| Watts | 2.78 | | | | 33.55 |
| CFM | 1804 | | | | 5330 |
| CFM/Watts | 648.92 | | | | 158.87 |